

1、8208T/8228T 图片



2、8208T/8228T 性能参数 Specification

● Overall Dimension 整机尺寸		
1	Length 整机长度	6505mm
2	Width(to outside of wheels)整机宽度	2390mm
3	Height(top of the cab)整机高度 (到驾驶室顶部)	3250mm
4	Wheel base 轴距	3230mm
5	Tread 轮距	1610mm
6	Min. ground clearance 最小离地间隙	410mm

● **Main Technical Specification 主要技术参数**

1	Static line force 静线压力 N/cm	474/509
2	Dynamic line force 动线压力 N/cm	1659/1831
3	Operating weight 整机重量 kg	20000/22000
4	Centrifugal Force 激振力 kN	350/270; 390/270
5	Frequency 频率 Hz	29/35; 28/32
6	Amplitude 幅度 mm	1.0/1.9; 1.1/2.1
7	Static Weight at Drum 分配在振动轮的重量 kg	10000/11000
8	Static Weight at Tires 分配在后轮的重量 kg	10000/11000
9	Min. turning radius(rear wheel)转弯半径 (后轮)	6800mm
10	Drum diameter 振动轮直径	1550mm
11	Drum width 振动轮宽度	2130/2150mm
12	Drum thickness 振动轮厚度	40/50mm
13	Traveling speed(Km/h),F2R2 行驶速度/前 3 后 2	2.5,4.88, 10.3/2.47,4.9
14	Gradient capacity 爬坡能力	30%

● **Diesel engine 发动机**

1	Model 型号	上柴 SC7H190.1G3
2	Type 形式	共轨、电喷、中冷
3	Rated output 额定功率	140 kW
4	Rated speed 额定转速	2000rpm
5	Max. Torque 最大扭矩	850(N.M)@1200~1500RPM
<ul style="list-style-type: none"> ● Driving System 驱动系统 		
1	Type 形式	机械单驱
2	Size of tire 轮胎尺寸	20.5-25-16PR
<ul style="list-style-type: none"> ● Working Hydraulic System 工作液压系统 		
1	Model of vibratory pump 振动泵型号	HPV02-A2-055R
2	System pressure 系统压力	42MPa
3	Model of vibratory motor 振动马达型号	HMF02-A2-055N
<ul style="list-style-type: none"> ● Steering System 转向系统 		
1	Model of steering pump 转向泵型号	QC25/16-226B (柴油机带)
2	Model of redirector 转向器型号	BZZ1-E500C
3	System pressure 系统压力	14MPa

● **Brake System 制动系统**

1	Type of service brake 行车制动形式	单管路、气顶液、钳盘式制动
2	Type of parking brake 停车制动形式	气控鼓式制动

Oil Capacity 用油量

1	Fuel(diesel)柴油	300 (L)
2	Engine lubricating oil 机油	20.5(L)
3	Oil for hydraulic system 液压油	140(L)
4	Oil for driving axles 驱动桥用油	24 (L)
5	变速箱用油	15 (L)
6	Oil for vibrating drum 振动轮用油	2X2.3(L)